

PERNOS HEXAGONALES GRADO 2 ROSCA UNC GALVANIZADO

NORMA DE FAB. ANSI B18.2.1
MATERIAL ACERO BAJO CARBONO
RESISTENCIA 74,000 PSI / 52 Kg/mm2
DUREZA 80-100 RB
ACABADO GALVANIZADO EN CALIENTE
PERNO 004

TUERCA

016



Largo / Ø	1/4	5/16	3/8	1/2	5/8	3/4
Tuerca	1.68	2.11	3.33	8.94	17.12	23.04
	0	0	0	0	0	0
7/8			7.56			
			0			
1	4.80		8.87	17.22		
	0		0	0		
1.1/4			10.34	18.54		
			0	0		
1.1/2	5.31	9.43	13.56	18.31	51.80	55.24
	0	0	0	0	0	0
1.3/4			15.16		48.52	58.23
			0		0	0
2	8.32	11.28	17.29	30.42	55.86	61.77
	0	0	0	0	0	0
2.1/2	9.20	14.63	17.89	30.48	62.83	80.17
	0	0	0	0	0	0
3	10.51		23.90	40.36	73.18	
	0		0	0	0	
3.1/2				40.44	80.84	
				0	0	
4	13.68	21.32	31.16	42.15		
	0	0	0	0		
4.1/2						145.68
						0
5		26.24	38.78	74.30	97.35	
		0	0	0	0	
6		31.86			114.61	
		0			0	
7					144.98	
					0	
13					291.17	
					0	
14					295.44	
					0	
18					358.80	
					0	
HPP	20	18	16	13	11	10

* LOS VALORES DE VENTA SE ENTIENDE POR 100 PIEZAS Y PUESTOS EN LIMA

Largo / Ø	1	7/8	1.1/4	1.1/2
Tuerca	50.50	34.20	146.94	203.41
	0	0	0	0

* LOS VALORES DE VENTA SE ENTIENDE POR 100 PIEZAS Y PUESTOS EN LIMA